



#### NOTES:

1. CLAY INFIELD MIX SHALL BE FREE OF ROCKS, DEBRIS, VEGETATION AND FOREIGN MATERIAL WITH 100% PASSING A 9mm SCREEN, 85% PASSING A 6mm SCREEN. INFIELD SUBGRADE SHALL BE STERILIZED AND TREATED WITH HERBICIDE TO PREVENT WEED GROWTH THROUGH THE INFIELD MIX. HERBICIDE SHALL BE APPROVED BY THE CITY SENIOR PARK SUPERVISOR PRIOR TO APPLICATION.
2. THE COMPOSITION OF THE INFIELD MIX SHALL BE AS FOLLOWS:  
 70% RED LAVA CINDER GRADED 1/8"  
 20% WILDER CLAY  
 10% MANTECA LOAM
3. SUBMIT A TWO QUART SAMPLE TO THE CITY REPRESENTATIVE FOR REVIEW AND APPROVAL PRIOR TO ORDER AND DELIVERY.
4. REFER TO DETAIL PSD SPORT-10 FOR ADJACENT EDGE BAND ALONG BACKSTOP AND FOUL LINE. CLAY INFIELD SURFACE AND MOWBAND ARE ALWAYS FLUSH UNLESS DELINEATED OTHERWISE.

0 2" 4" 8" 16"



SCALE: 1 1/2" = 1'-0"

## CITY OF FREMONT PARK STANDARD DETAILS INFIELD MATERIAL AND MOWBAND

DATE APPROVED BY CITY COUNCIL  
December 13, 2011

RESOLUTION NO. 2011-65

SENIOR LANDSCAPE ARCHITECT

*[Signature]*

COMMUNITY SERVICES DIRECTOR

*[Signature]*

APR.	REVISED	DATE
REVISIONS		

FILE NO.	SCALE	DRAWN	CHECKED	DATE	DWG NO.	
PSD SPORT-11.DWG	1 1/2" = 1'-0"	MAM	RER	03/28/2011	PSD SPORT-11	1 OF 1